


<b>Pneumatic Hog Ring</b>							
<b>Type 15100</b>							
<b>Description:</b> The 15100 hog ring is a very popular hog ring and most widely used style we make. It is available in a wide variety of high quality alloys of wire and then taped together with high strength polyester tape. It features blunt tips to promote safety or sharp tips when piercing capabilities are required.							
<b>Popular applications:</b> Bedding, Automotive Seating, Animal Cages, Bungee Cords, Insulation, Silt Fence, Bag Closure, Nursery, Crafts	<table border="1"> <tr> <td>Open:</td> <td>3/4" Crown (0.750" / 19.05mm)</td> </tr> <tr> <td>Closed:</td> <td>5/16" Diameter (0.3125" / 7.94mm)</td> </tr> <tr> <td>Wire:</td> <td>15 gauge (0.0720" / 1.83mm)</td> </tr> </table>	Open:	3/4" Crown (0.750" / 19.05mm)	Closed:	5/16" Diameter (0.3125" / 7.94mm)	Wire:	15 gauge (0.0720" / 1.83mm)
Open:	3/4" Crown (0.750" / 19.05mm)						
Closed:	5/16" Diameter (0.3125" / 7.94mm)						
Wire:	15 gauge (0.0720" / 1.83mm)						

Type description:	<b>15100 Hog Ring Pneumatic Model</b>
Article code:	P960009
Application Tool:	SC7/SC7C (pneumatic)
Ring Design:	C style
Material Options:	Bright, Stainless, Galvanized
Points:	Sharp or Blunt
Fasteners per strip:	100 rings
Fasteners per box:	10,000 rings
Weight per box:	17.0 lbs (7.71 kg)
Boxes per skid:	100 boxes
Weight per skid:	1700 lbs (771.11 kg)

**Accessories:**

Article code	Description
HRT960009	SC7 Pneumatic Hog Ring Application Tool
HRT960009C	SC7C Pneumatic Hog Ring Application Tool
HRT960009CRT	CRT23-LN Pneumatic Hog Ring Application Tool